

# Submittal Data Sheet

**Panasonic**

Series Name: Hyper Heat AHU Series  
 Model Number: CS-HM30BAHU/CU-HM30BAHU

## AIR HANDLER HEAT PUMP SYSTEM

Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



## INDOOR SPECIFICATION

Indoor Air Flow	988.8 / 894.7 / 806.4 / 712.2 /	
Indoor Noise Level (Turbo/H/M/L)	47.0/46.0/43.0/27.5/N/A	
Dimension (WxDxH)	inch	21.02 x 21.02 x 49.02
	mm	534.0x534.0x1245.0
Package (WxDxH)	inch	26.57 x 24.41 x 52.56
	mm	675x620x1335
Net/Gross	lbs	128.97/153.44
Weight	kg	58.5/69.6

## OUTDOOR SPECIFICATION

Compressor Type	ROTARY	
Compressor Model	MTH356UKRC8FQL	
Refrigerant	R454B	
Refrigerant Oil Charge(mL)	1300	
Refrigerant Oil	HAF68D1A	
Outdoor Air Flow (Max) (CFM)	3001.8	
Outdoor Noise Level (dBA)	60.5	
Dimension (WxDxH)	inch	37.24 x 16.14 x 31.89
	mm	946.0x410.0x810.0
Package (WxDxH)	inch	42.91 x 19.68 x 34.84
	mm	1090x500x885
Net/Gross	lbs	164.02/174.60
Weight	kg	74.4/79.2

## EFFICIENCY

Cooling		Heating	
SEER2	16.8	HSPF2-4	10.0
EER2	11.7	COP	3.65

## PERFORMANCE of Cooling

Cooling (Btu/hr)	
Rated Capacity	30000
Min/Max Capacity	12800-39000
Moisture Removal(L/h)	2.77
Standard Operating Range(°F)	-22~122(-30~50)
Rated Cooling Conditions:	Indoor: 80°F DB/67°F WB Outdoor: 95°F DB/75°F WB

## PERFORMANCE of Heating

Heating (Btu/hr)	
1. @ 47°F Rated	34000
2. @ 47°F Min/Max Capacity	10300-38500


## ELECTRICAL

Indoor Power Supply	115/208/230V,60Hz,1Ph
Indoor MCA 115V/(208/230V)	8.0/6.0
Indoor MOP	15
Outdoor Power Supply	208/230V,60Hz,1Ph
Outdoor MCA	29.5
Outdoor MOP	30
Communication Wiring	AWG 20-2
Compressor RLA	22.4
Outdoor Fan Motor RLA	1.5
Outdoor Fan Motor W	120
Indoor Fan Motor RLA	4.5
Indoor Fan Motor W	375
System Power Input @ Cooling (W)	2567(850 ~ 3620)
System Power Input @ Heating (W)	2790(655 ~ 3020)
MCA: Min. circuit amps (A)	CP: Max. over current protector
RLA: Rated load amps (A)	W: Fan motor rated output (W)

<b>3. @ 17°F Rated</b>	23800
<b>4. @ 5°F Rated: Capacity / COI</b>	32600/1.96
<b>5. @ 5°F Max: Capacity</b>	32600
<b>Standard Operating Range(°F)</b>	-22~75(-30~24)
1. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 47°F DB/43°F WB
2. Rated Heating Conditions:	Indoor: 70°F DB/60°F WB Outdoor: 17°F DB/15°F WB
3. Heating Conditions, Compre	Indoor: 70°F DB/60°F WB
Operating at Max. Frequency	Outdoor: 5°F DB/5°F WB


PIPING	
Throttle type(Indoor)	EXV
Throttle type(Outdoor)	EXV
Liquid Size	9.52mm(3/8in)
Gas Size	19mm(3/4in)
Max. Piping Length(ft/m)	164(50)
Max. Height Difference(ft/m)	82(25)
Max. Pre-charged Length(ft/m)	24.6(7.5)
Refrigerant Pre-charged Amount(oz/kg)	105.82(3)
Additional Charge of Refrigerant((oz/ft)/(g/m))	0.7(65)
Connection Method	Flared

# INDOOR UNIT DIMENSIONS




Dimensions \ Model		18k/24k		30k/36k		48k/60k	
		inch	mm	inch	mm	inch	mm
A	Model Height	45	1143	49	1245	53	1346
B	Model Width	17-1/2	445	21	534	24-1/2	622
C	Supply Air Opening Width	15-5/8	397	19-1/8	486	22-5/8	575
D	Return Air Opening Width	15-1/8	384	18-5/8	473	22-1/8	562
E	Model Depth	21	534	21	534	21	534
F	Supply Air Opening Depth	10-1/4	260	10-1/4	260	10-1/4	260
G	Return Air Opening Depth	18-3/4	476	18-3/4	476	18-3/4	476
H	Supply Air Opening Clearance	15/16	24	15/16	24	15/16	24
I	Return Air Opening Side Clearance	1-1/4	32	1-1/4	32	1-1/8	28
J	Return Air Opening Front Clearance	1-1/2	38	1-5/8	41	1-5/8	41
K	Return Air Opening Back Clearance	5/8	16	5/8	16	3/4	19

## OUTDOOR UNIT DIMENSIONS




## INSTALLATION INSTRUCTIONS FOR OUTDOOR UNIT



- Meets all spatial requirements shown in Installation Clearance Requirements above.

## FEATURES



## Features

- Multi-position installation: horizontal(left or right), vertical( up or down)
- Aluminum Coil
- Constantly Air Flow system up to 0.80 In.W.G
- 1 inch R4.2 fiberglass free insulation reduces condensation and boosts efficiency(optional)
- Optional Auxiliary heat kit up to 25kW
- Easy Maintenance
- Multiple control options available:
  - Two way communication wired controller:120N(X6)
  - Two way communication wired controller with built-in WiFi:120N(X6W)
  - Wireless remote controller
  - Third-Party 24V Thermostat
- Adaptive Control System
- High efficiency up to 19 SEER2, 12.5 EER2, 10.3 HSPF2
- 100% heat output at -4F\*
- Chassis heater and crankcase heater equipped as standard

\* For 36K model, rated cooling capacity/heating capacity at -4F=100%